

## 1. IDENTIFICATION OF THE SUBSTRATE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

Trade name/designation: Eurorooft PU Insulation Spray Adhesive.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Adhesive.

### 1.3 Supplier details

Alumasc Building Products Ltd  
White House Works, Bold Road, Sutton, St Helens, Merseyside, United Kingdom, WA9 4JG  
Tel: +44 (0)1744 648400  
e-mail: [technical@alumascroofing.com](mailto:technical@alumascroofing.com)

### 1.4 Emergency telephone number

Association / Organisation: National Poisons Information Service  
Emergency telephone numbers: 0344 892 0111 (Healthcare professionals only)  
Other emergency telephone numbers Alumasc Building Products: +44 17 4464 8400  
(Mon-Thurs – 08.30-17.00 Fri – 08.30-16.00)

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

Considered a hazardous mixture according to Reg. (EC) No 1272/2008 and their amendments. Classified as Dangerous Goods for transport purposes.

#### Classification according to Regulation (EC) No. 1272/2008 [CLP][1]:

H334 - Sensitisation (Respiratory) Category 1, H319 - Serious Eye Damage/Eye Irritation Category 2, H317 - Sensitisation (Skin) Category 1, H351 - Carcinogenicity Category 2.

#### Legend:

1. Classified by Chemwatch; 2. Classification drawn from GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567

### 2.2 Label elements

#### Hazard pictures:



#### Signal word:

Danger.

#### Hazard statements:

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.

#### Supplementary statements:

EUH044 Risk of explosion if heated under confinement.  
EUH204 Contains isocyanates. May produce an allergic reaction.

#### Precautionary statements prevention:

P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe gas.  
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P284 [In case of inadequate ventilation] wear respiratory protection.  
P272 Contaminated work clothing should not be allowed out of the workplace.

Precautionary statements response: P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P308+P313 IF exposed or concerned: Get medical advice/ attention.  
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician/first aider.  
P302+P352 IF ON SKIN: Wash with plenty of water and soap.  
P305+P351+P338IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 Get medical advice/attention if you feel unwell.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.

Precautionary statements storage: P405 Store locked up.  
P410+P403 Protect from sunlight. Store in a well-ventilated place.

Precautionary statements disposal: P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

### 2.3 Other hazards

Polymeric Diphenylmethane Diisocyanate: Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply).

## 3. COMPOSITION AND INFORMATION ABOUT THE COMPONENTS

### 3.1 Substances

See 'Composition on ingredients' in Section 3.2.

### 3.2 Mixtures

1. CAS No 2. EC No 3. Index No 4. REACH No	% [weight]	Name	Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	Nanoform Particle Characteristics
1. 29118-24-9 2. Not available 3. Not available 4. Not available	10-30	1,3,3,3-Tetrafluoropropene	Gases Under Pressure (Liquefied Gas); H280, EUH044 [1]	Not available
1. 9016-87-9 2. Not available 3. Not available 4. Not available	5-15	Polymeric Diphenylmethane Diisocyanate	Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Sensitisation (Skin) Category 1, Sensitisation (Respiratory) Category 1, Carcinogenicity Category 2, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Specific Target Organ Toxicity - Repeated Exposure Category 2; H332, H315, H319, H317, H334, H351, H335, H373, EUH204 [1]	Not available
1. 7727-37-9 2. 231-783-9 3. Not available 4. Not available	<1	Nitrogen	Gases Under Pressure (Compressed Gas); H280, EUH044 [1]	Not available
<b>Legend:</b>	1. Classified by Chemwatch; 2. Classification drawn from GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties			

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

- Eye contact:** If product comes in contact with eyes remove the patient from gas source or contaminated area. Take the patient to the nearest eye wash, shower or other source of clean water.  
Open the eyelid(s) wide to allow the material to evaporate.  
Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners.  
The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage.  
Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s) Transport to hospital or doctor.  
Even when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur. If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage.  
Ensure verbal communication and physical contact with the patient.  
**DO NOT** allow the patient to rub the eyes  
**DO NOT** allow the patient to tightly shut the eyes  
**DO NOT** introduce oil or ointment into the eye(s) without medical advice  
**DO NOT** use hot or tepid water.
- Skin contact:** If skin contact occurs:  
Immediately remove all contaminated clothing, including footwear.  
Flush skin and hair with running water (and soap if available).  
Seek medical attention in event of irritation.
- Inhalation:** Following uptake by inhalation, move person to an area free from risk of further exposure. Oxygen or artificial respiration should be administered as needed. Asthmatic-type symptoms may develop and may be immediate or delayed up to several hours. Treatment is essentially symptomatic. A physician should be consulted.  
Following exposure to gas, remove the patient from the gas source or contaminated area.  
NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer.  
Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures. If the patient is not breathing spontaneously, administer rescue breathing. If the patient does not have a pulse, administer CPR.  
If medical oxygen and appropriately trained personnel are available, administer 100% oxygen.  
Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further instruction.  
Keep the patient warm, comfortable and at rest while awaiting medical care.  
**MONITOR THE BREATHING AND PULSE, CONTINUOUSLY.**  
Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if necessary.
- Ingestion:** Not considered a normal route of entry.  
Avoid giving milk or oils.  
Avoid giving alcohol.

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11.

### 4.3 Indication of any immediate medical attention and special treatment needed.

#### For intoxication due to Freons/ Halons:

##### A: Emergency and Supportive Measures

- Maintain an open airway and assist ventilation if necessary.
- Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
- Monitor the ECG for 4-6 hours.

##### B: Specific drugs and antidotes:

- There is no specific antidote

**C: Decontamination**

- Inhalation; remove victim from exposure, and give supplemental oxygen if available.
- Ingestion; (a) Prehospital: Administer activated charcoal, if available. DO NOT induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital: Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes).

**D: Enhanced elimination:**

- There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal.

POISONING and DRUG OVERDOSE, Californian Poison Control System Ed. Kent R Olson; 3rd Edition

- Do not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability. No specific antidote.
- Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician.
- If lavage is performed, suggest endotracheal and/or esophageal control.
- Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
- Treatment based on judgment of the physician in response to reactions of the patient

**For frost-bite caused by liquefied petroleum gas:**

- If part has not thawed, place in warm water bath (41-46 C) for 15-20 minutes, until the skin turns pink or red. Analgesia may be necessary while thawing.
- If there has been a massive exposure, the general body temperature must be depressed, and the patient must be immediately rewarmed by whole-body immersion, in a bath at the above temperature.
- Shock may occur during rearming.
- Administer tetanus toxoid booster after hospitalization. Prophylactic antibiotics may be useful.
- The patient may require anticoagulants and oxygen.

[Shell Australia 22/12/87].

**For gas exposures:**

**Basic treatment:**

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.

**Advanced treatment:**

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications. Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

**For sub-chronic and chronic exposures to isocyanates:**

- This material may be a potent pulmonary sensitiser which causes bronchospasm even in patients without prior airway hyperreactivity.
- Clinical symptoms of exposure involve mucosal irritation of respiratory and gastrointestinal tracts.
- Conjunctival irritation, skin inflammation (erythema, pain vesiculation) and gastrointestinal disturbances occur soon after exposure. Pulmonary symptoms include cough, burning, substernal pain and dyspnoea.
- Some cross-sensitivity occurs between different isocyanates.
- Noncardiogenic pulmonary oedema and bronchospasm are the most serious consequences of exposure. Markedly symptomatic patients should receive oxygen, ventilatory support and an intravenous line.
- Treatment for asthma includes inhaled sympathomimetics (epinephrine [adrenalin], terbutaline) and steroids.
- Activated charcoal (1 g/kg) and a cathartic (sorbitol, magnesium citrate) may be useful for ingestion.
- Mydriatics, systemic analgesics and topical antibiotics (Sulamyd) may be used for corneal abrasions.
- There is no effective therapy for sensitised workers.

[Ellenhorn and Barceloux; Medical Toxicology].

**NOTE:** Isocyanates cause airway restriction in naive individuals with the degree of response dependant on the concentration and duration of exposure. They induce smooth muscle contraction which leads to bronchoconstrictive episodes. Acute changes in lung function, such as decreased FEV1, may not represent sensitivity.

[Karol & Jin, Frontiers in Molecular Toxicology, pp 56-61, 1992].

Personnel who work with isocyanates, isocyanate prepolymers or polyisocyanates should have a pre-placement medical examination and periodic examinations thereafter, including a pulmonary function test. Anyone with a medical history of chronic respiratory disease, asthmatic or bronchial attacks, indications of allergic responses, recurrent eczema or sensitisation conditions of the skin should not handle or work with isocyanates. Anyone who develops chronic respiratory distress when working with isocyanates should be removed from exposure and examined by a physician. Further exposure must be avoided if a sensitivity to isocyanates or polyisocyanates has developed.

## 5. FIRE-FIGHTING MEASSURES

### 5.1 Extinguishing media

- Small quantities of water in contact with hot liquid may react violently with generation of a large volume of rapidly expanding hot sticky semi-solid foam.
- Presents additional hazard when fire fighting in a confined space.
- Cooling with flooding quantities of water reduces this risk.

#### Small fire:

Use extinguishing agent suitable for type of surrounding fire.

#### Large Fire:

Cool cylinder.

**DO NOT** direct water at source of leak or venting safety devices as icing may occur.

### 5.2 Special hazards arising from the substance or mixture

#### Fire incompatibility:

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

### 5.3 Advice for fire-fighters

#### Fire-fighting:

- Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.

#### Fire/explosion hazard:

- Combustible.
- Moderate fire hazard when exposed to heat or flame.
- When heated to high temperatures decomposes rapidly generating vapour which pressures and may then rupture containers with release of flammable and highly toxic isocyanate vapour.

Decomposition may produce toxic fumes of:

- carbon monoxide (CO)

Combustion products include:

- carbon dioxide (CO<sub>2</sub>)
- isocyanates
- hydrogen cyanide
- and minor amounts of nitrogen oxides (NO<sub>x</sub>)
- hydrogen fluoride

other pyrolysis products typical of burning organic material.

**Contains low boiling substance:** Closed containers may rupture due to pressure buildup under fire conditions.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

See Section 8.

### 6.2 Environmental precautions

See Section 12.

### 6.3 Methods and material for containment and cleaning up

#### Minor spills:

- Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used.
- DO NOT enter confined spaces where gas may have accumulated.

#### Major spills:

##### For isocyanate spills of less than 40 litres (2 m<sup>2</sup>):

- Evacuate area from everybody not dealing with the emergency, keep them upwind and prevent further access, remove ignition sources and, if inside building, ventilate area as well as possible.
- Notify supervision and others as necessary.
- Put on personal protective equipment (suitable respiratory protection, face and eye protection, protective suit, gloves and impermeable boots).
- Avoid contamination with water, alkalies and detergent solutions.
- Material reacts with water and generates gas, pressurises containers with even drum rupture resulting.
- **DO NOT reseal container if contamination is suspected.**
- Clear area of all unprotected personnel and move upwind.
- Alert Emergency Authority and advise them of the location and nature of hazard. Wear breathing apparatus and protective gloves.
- Remove leaking cylinders to a safe place.
- Fit vent pipes. Release pressure under safe, controlled conditions Burn issuing gas at vent pipes.
- **DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.**

### 6.4 Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

#### Safe handling:

- Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature
- The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines.
- Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended
- **DO NOT transfer gas from one cylinder to another.**

#### Fire & explosion protection:

See Section 5.

#### Other information:

Consider storage under inert gas.

- Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open. Such compounds should be sited and built in accordance with statutory requirements.
- The storage compound should be kept clear and access restricted to authorised personnel only.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Suitable container:








- Cylinder:
- Ensure the use of equipment rated for cylinder pressure. Ensure the use of compatible materials of construction.
- Valve protection cap to be in place until cylinder is secured, connected.

#### Storage incompatibility:

- As a general rule, hydrofluorocarbons tend to be flammable unless they contain more fluorine atoms than hydrogen atoms.
- Haloalkenes are highly reactive.
  - Some of the more lightly substituted lower members are highly flammable; many members of the group are peroxidisable and polymerisable.
  - Avoid reaction or contact with potassium or its alloys - although apparently stable on contact with a wide range of halocarbons, reaction products may be shock-sensitive and may explode with great violence on light impact.

Avoid reaction with water, alcohols and detergent solutions. Isocyanates are electrophiles, and as such they are reactive toward a variety of nucleophiles including alcohols, amines, and even water. Upon treatment with an alcohol, an isocyanate forms a urethane linkage.

- A range of exothermic decomposition energies for isocyanates is given as 20-30 kJ/mol.
- The relationship between energy of decomposition and processing hazards has been the subject of discussion; it is suggested that values of energy released per unit of mass, rather than on a molar basis (J/g) be used in the assessment.
- For example, in "open vessel processes" (with man-hole size openings, in an industrial setting), substances with exothermic decomposition energies below 500 J/g are unlikely to present a danger, whilst those in "closed vessel processes" (opening is a safety valve or bursting disk) present some danger where the decomposition energy exceeds 150 J/g.
- Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances

						
+	X	+	O	+	+	+

X - Must not be stored together.

O - May be stored together with specific preventions.

+ - May be stored together.

**Note:** Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

### 7.3 Specific end uses(s)

See Section 1.2.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
1,3,3,3-Tetrafluoropropene	Inhalation 3 902 mg/m <sup>3</sup> (Systemic, Chronic) Inhalation 830 mg/m <sup>3</sup> (Systemic, Chronic) *	0.1 mg/L (Water (Fresh)) 1 mg/L (Water (Marine))

\* Values for general population.

### Occupational Exposure Limits (OEL):

#### Ingredient data:


Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Europe ECHA Occupational exposure limits - Activity list	Polymeric Diphenylmethane Diisocyanate	Not available	Not available	Not available	Not available	Not available
UK Workplace Exposure Limits (WELs)	Polymeric Diphenylmethane Diisocyanate	Isocyanates, all (as -NCO) except Methyl Isocyanate	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	Not available	Sen

#### Emergency limits:

Ingredient	TEEL-1	TEEL-2	TEEL-3
1,3,3,3-Tetrafluoropropene	1,400 ppm	Not available	Not available
Polymeric Diphenylmethane Diisocyanate	0.15 mg/m <sup>3</sup>	3.6 mg/m <sup>3</sup>	22 mg/m <sup>3</sup>
Nitrogen	7.96E+05 ppm	8.32E+05 ppm	8.69E+05 ppm

Ingredient	Original IDLH	Revised IDLH
1,3,3,3-Tetrafluoropropene	Not available	Not available
Polymeric Diphenylmethane Diisocyanate	Not available	Not available
Nitrogen	Not available	Not available

## 8.2 Exposure controls

8.2.1. Appropriate engineering Controls:	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk.
8.2.2. Personal protection:	
Eye and face protection:	Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection:	See Hand Protection below.
Hands/feet protection:	<b>NOTE:</b> The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. Isocyanate resistant materials include Teflon, Viton, nitrile rubber and some PVA gloves. Protective gloves and overalls should be worn as specified in the appropriate national standard. Contaminated garments should be removed promptly and should not be re-used until they have been decontaminated. When handling sealed and suitably insulated cylinders wear cloth or leather gloves.
Body protection:	See Other Protection below.
Other protection:	Protective overalls, closely fitted at neck and wrist. Eye-wash unit. Ensure availability of lifeline in confined spaces.

### Respiratory protection:

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.

The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate. Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)

Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

### 8.2.3. Environmental exposure controls

See Section 12.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Important health, safety and environmental information

<b>Appearance:</b>	Moisture sensitive Cream		
<b>Physical state:</b>	Compressed Gas	<b>Relative density (Water = 1):</b>	1.14-1.20
<b>Odour:</b>	Not applicable	<b>Partition coefficient n-octanol/water:</b>	Not applicable
<b>Odour threshold:</b>	Not available	<b>Auto-ignition temperature (°C):</b>	Not applicable
<b>pH (as supplied):</b>	Not available	<b>Decomposition temperature:</b>	Not applicable
<b>Melting point/freezing point (°C):</b>	Not applicable	<b>Viscosity (cSt):</b>	2083.333-2916.667
<b>Initial boiling point and boiling range (°C):</b>	Not applicable	<b>Molecular weight (g/mol):</b>	Not applicable
<b>Flash point (°C):</b>	Not applicable	<b>Taste:</b>	Not applicable
<b>Evaporation rate:</b>	Not applicable	<b>Explosive properties:</b>	Not applicable
<b>Flammability:</b>	Not available	<b>Oxidising properties:</b>	Does not meet criteria for classification as oxidising
<b>Upper Explosive Limit (%):</b>	Not available	<b>Surface Tension (dyn/cm or mN/m):</b>	Not applicable
<b>Lower Explosive Limit (%):</b>	Not available	<b>Volatile Component (%vol):</b>	Not applicable
<b>Vapour pressure (kPa):</b>	Not available	<b>Gas group:</b>	Not applicable
<b>Solubility in water:</b>	Immiscible	<b>pH as a solution (1%):</b>	Not applicable
<b>Vapour density (Air = 1):</b>	Not available	<b>VOC g/L:</b>	Not applicable
<b>Nanoform Solubility:</b>	Not available	<b>Nanoform Particle Characteristics:</b>	Not applicable
<b>Particle Size:</b>	Not available		

### 9.2 Other information

Not applicable.

## 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

See Section 7.2.

### 10.2 Chemical stability

- Unstable in the presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

### 10.3 Possibility of hazardous reactions

See Section 7.2.

### 10.4 Conditions to avoid

See Section 7.2.

### 10.5 Incompatible materials

See Section 7.2.

### 10.6 Hazardous decomposition products

See Section 5.3

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Inhaled:	<p>The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.</p> <p>Exposure to fluorocarbons can produce non-specific flu-like symptoms such as chills, fever, weakness, muscle pain, headache, chest discomfort, sore throat and dry cough with rapid recovery. High concentrations can cause irregular heartbeats and a stepwise reduction in lung capacity.</p> <p>Inhalation of non-toxic gases may cause: CNS effects: headache, confusion, dizziness, stupor, seizures and coma; respiratory: shortness of breath and rapid breathing; cardiovascular: collapse and irregular heartbeats; gastrointestinal: mucous membrane irritation, nausea and vomiting.</p> <p>The vapour/mist may be highly irritating to the upper respiratory tract and lungs; the response may be severe enough to produce bronchitis and pulmonary oedema. Possible neurological symptoms arising from isocyanate exposure include headache, insomnia, euphoria, ataxia, anxiety neurosis, depression and paranoia. Gastrointestinal disturbances are characterised by nausea and vomiting.</p> <p>Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p>
Ingestion:	<p>Not normally a hazard due to physical form of product.</p> <p>Considered an unlikely route of entry in commercial/industrial environments</p> <p>Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal.</p>
Skin contact:	<p>This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition.</p> <p>Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.</p> <p>Fluorocarbons remove natural oils from the skin, causing irritation, dryness and sensitivity. Open cuts, abraded or irritated skin should not be exposed to this material.</p> <p>Entry into the blood-stream, through for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.</p>
Eye:	<p>Not considered to be a risk because of the extreme volatility of the gas.</p> <p>This material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure.</p>
Chronic:	<p>There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>This product contains a polymer with a functional group considered to be of high concern. Isothiocyanates may cause hypersensitivity of the skin and airways.</p> <p>The reactivity of an epoxide intermediate may be the reason for the cancer-causing properties of halogenated oxiranes. It is reported that 1,1-dichloroethyne, vinyl chloride, trichloroethylene, tetrachloroethylene and chloroprene all cause cancer.</p> <p>Generally speaking, substances with one halogen substitution show higher potential to cause cancer compared to substances with two. Main route of exposure to the gas in the workplace is by inhalation. Persons with a history of asthma or other respiratory problems or are known to be sensitised, should not be engaged in any work involving the handling of isocyanates.</p> <p>The chemistry of reaction of isocyanates, as evidenced by MDI, in biological milieu is such that in the event of a true exposure of small MDI doses to the mouth, reactions will commence at once with biological macromolecules in the buccal region and will continue along the digestive tract prior to</p>

	reaching the stomach. Reaction products will be a variety of polyureas and macromolecular conjugates with for example mucus, proteins and cell components. Animal testing shows that polymeric MDI can damage the nasal cavities and lungs, causing inflammation and increased cell growth.
--	--

**Euroroof Insulation Adhesive:**

Toxicity	Irritation
Not available	Not available

**1,3,3,3-Tetrafluoropropene:**

Toxicity	Irritation
Inhalation(Rat) LC50; >1157.752 ppm4h[2]	Not available

**Polymeric Diphenylmethane Diisocyanate:**

Toxicity	Irritation
Dermal (rabbit) LD50: >9400 mg/kg[2]	Eye (rabbit): 100 mg - mild
Inhalation(Rat) LC50; 0.49 mg/L4h[2]	
Oral(Rat) LD50; 43000 mg/kg[2]	

**Nitrogen:**

Toxicity	Irritation
Not available	Not available

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity; 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances.

1,3,3,3- Tetrafluoropropene:	Inhalation (rat) NOEL (28 days): >1.5 mg/l ** Vendor HFO-1234ze is not likely to accumulate in the bodies of humans or animals HFO-1234ze is practically non-toxic. Short-term exposures at levels higher than 10% have not induced cardiac sensitization to adrenalin nor induced serious toxic effects. Rats and rabbits did not exhibit any serious toxic, developmental or reproductive effects even with exposures to high levels of HFO-1234ze. Based on a series of mutagenicity and genomics studies, the cancer risk for HFO-1234ze is low, no cardiac sensitisation was observed in dogs with exposures up to 120,000 ppm; repeated dose toxicity in rats (13-wk) found mild effects on the heart (NOEL 5,000ppm); in vitro genotoxicity findings include negative Ames Test and negative human lymphocyte chromosome aberration test; in vivo genotoxicity findings in the mouse micronucleus test were negative (inhalation, mammalian bone-marrow cytogenic test with chromosomal analysis).
Polymeric Diphenylmethane Diisocyanate:	product Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Aromatic and aliphatic diisocyanates may cause airway toxicity and skin sensitization. Monomers and prepolymers exhibit similar respiratory effect. Of the several members of diisocyanates tested on experimental animals by inhalation and oral exposure, some caused cancer while others produced a harmless outcome. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
Euroroof Insulation Adhesive & Polymeric Diphenylmethane Diisocyanate:	Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more prone than others, and exposure to other irritants may aggravate symptoms. Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema. Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (Tlymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure. The following information refers to contact allergens as a group and may not be specific to this product.

	Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.
Euroroof Insulation Adhesive & 1,3,3,3-Tetrafluoropropene:	Inhalation of perfluoroalkenes can cause lung injury, kidney damage, brain changes and death. Repeated exposures may alter blood pressure and the production of blood cells. The potential for causing cancer is the subject of speculation. Fluoroalkanes, in contrast, are less toxic. Disinfection byproducts (DBPs) are formed when disinfectants such as chlorine, chloramines and ozone react with organic and inorganic matter in water. Animal studies have shown that some DBPs cause cancer. To date, several hundred DBPs have been identified. Numerous haloalkanes and haloalkenes have been tested for cancer-causing and mutation-causing activities.

Acute Toxicity	✗	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin Sensitisation	✓	STOT - Repeated Exposure	✓
Mutagenicity	✗	Aspiration Hazard	✗

**Legend:**

- ✗ - Data either not available or does not fill the criteria for classification.
- ✓ - Data available to make classification.

**11.2.1. Endocrine Disruption Properties**

Not available.

**12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

**Euroroof Insulation Adhesive:**

End point	Test duration (Hr)	Species	Value	Source
Not available	Not available	Not available	Not available	Not available

**1,3,3,3-Tetrafluoropropene:**

End point	Test duration (Hr)	Species	Value	Source
EC50	72h	Algae or other aquatic plants	>170mg/l	2
EC50	48h	Crustacea	>160mg/l	2
EC50(ECx)	48h	Crustacea	>160mg/l	2
EC50	72h	Algae or other aquatic plants	>170mg/l	2

**Polymeric Diphenylmethane Diisocyanate:**

End point	Test duration (Hr)	Species	Value	Source
Not available	Not available	Not available	Not available	Not available

**Nitrogen:**

End point	Test duration (Hr)	Species	Value	Source
Not available	Not available	Not available	Not available	Not available

**Legend:**

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data.

**For Polyisocyanates:**

Polyisocyanates are not readily biodegradable. However, due to other elimination mechanisms (hydrolysis, adsorption), long retention times in water are not to be expected. The resulting polyurea is more or less inert and, due to its molecular size, not bioavailable.

Substances containing unsaturated carbons are ubiquitous in indoor environments. They result from many sources (see below). Most are reactive with environmental ozone and many produce stable products which are thought to adversely affect human health. The potential for surfaces in an enclosed space to facilitate reactions should be considered.

In addition to carbon dioxide (CO<sub>2</sub>), methane (CH<sub>4</sub>) and nitrous oxide (N<sub>2</sub>O), the greenhouse gases mentioned in the Kyoto Protocol include synthetic substances that share the common feature of being highly persistent in the atmosphere and inhibit radiation from escaping out of the atmosphere. These synthetic substances include hydrocarbons that are partially fluorinated (HCFs) or totally fluorinated (PFCs) as well as sulfur hexafluoride (SF<sub>6</sub>). The greenhouse potential of these substances, expressed as multiples of that of CO<sub>2</sub>, are within the range of 140 to 11,700 for HFCs, from 6500 to 9,200 for PFCs and 23,900 for SF<sub>6</sub>.

**For Isocyanate Monomers:**

Environmental Fate: Isocyanates, (di- and polyfunctional isocyanates), are commonly used to make various polymers, such as polyurethanes. Polyurethanes find significant application in the manufacture of rigid and flexible foams. They are also used in the production of adhesives, elastomers, and coatings.

**DO NOT discharge into sewer or waterways.**

**12.2 Persistence and degradability**

No data available for all ingredients.

**12.3 Bioaccumulation potential**

No data available for all ingredients.

**12.4 Mobility in soil**

No data available for all ingredients.

**12.5 Results of PBT and vPvB assessment**

	<b>P</b>	<b>B</b>	<b>T</b>
Relevant available data	Not available	Not available	Not available
PBT	✗	✗	✗
vPvB	✗	✗	✗

PBT Criteria fulfilled?	No
vPvB	No

**12.6 Endocrine disruption properties**

Not available.

**12.7. Other adverse effects**

Not available.

**13. DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods**

Product / packaging disposal:	Evaporate residue at an approved site. Return empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase.
Waste treatment options:	Not available.
Sewage disposal options:	Not available.

## 14. TRANSPORT INFORMATION

### Labels required:



Marine Pollutant: No.

Hazchem: 2ZE.

### Land transport (ADR):

14.1 UN number	3500
14.2 UN proper shipping name	CHEMICAL UNDER PRESSURE, N.O.S. (contains polymeric diphenylmethane diisocyanate and nitrogen)
14.3 Transport hazard class(es)	Class: 2.2 Subrisk: Not applicable
14.4 Packing group	Not applicable
14.5 Environmental hazard	Not applicable
14.6 Special precautions for user	Hazard identification (Kemler): 20 Classification code: 8A Hazard label: 2.2 Special provisions: 274 659 Limited quantity: 0 Tunnel restriction code: 3 (C/E)

### Air transport (ICAO-IATA/DGR):

14.1 UN number	3500
14.2 UN proper shipping name	CHEMICAL UNDER PRESSURE, N.O.S. (contains polymeric diphenylmethane diisocyanate and nitrogen)
14.3 Transport hazard class(es)	ICAO/IATA class: 2.2 ICAO/IATA subrisk: Not applicable ERG code: 2 L
14.4 Packing group	Not applicable
14.5 Environmental hazard	Not applicable
14.6 Special precautions for user	Special provisions: A187 Cargo only packing instruction: 218 Cargo only maximum qty/pack: 150kg Passenger and cargo packing instruction: 218 Passenger and cargo maximum qty/pack: 75kg Passenger and cargo limited qty packing instructions: Forbidden Passenger and cargo limited maximum qty/pack: Forbidden

### Sea transport (IMDG-Code/GGVSee):

14.1 UN number	3500
14.2 UN proper shipping name	CHEMICAL UNDER PRESSURE, N.O.S. (contains polymeric diphenylmethane diisocyanate and nitrogen)
14.3 Transport hazard class(es)	IMDG class: 2.2 IMDG subrisk: Not applicable
14.4 Packing group	Not applicable
14.5 Environmental hazard	Not applicable
14.6 Special precautions for user	EMS number: F-C , S-V Special provisions: 274 362 Limited quantities: 0

### Inland waterways transport (ADN):

14.1 UN number	3500
14.2 UN proper shipping name	CHEMICAL UNDER PRESSURE, N.O.S. (contains polymeric diphenylmethane diisocyanate and nitrogen)
14.3 Transport hazard class(es)	2.2 Not applicable
14.4 Packing group	Not applicable
14.5 Environmental hazard	Not applicable

14.6 Special precautions for user	Classification code:	8A
	Special provisions:	274 659
	Limited quantity:	0
	Equipment required:	PP
	Fire cones numbers:	0

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC code

Not applicable.

#### 14.8. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product Name	Group
1,3,3,3-Tetrafluoropropene	Not available
Polymeric Diphenylmethane Diisocyanate	Not available
Nitrogen	Not available

#### 14.9. Transport in bulk in accordance with the ICG Code

Product Name	Ship Type
1,3,3,3-Tetrafluoropropene	Not available
Polymeric Diphenylmethane Diisocyanate	Not available
Nitrogen	Not available

### 15. REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 1,3,3,3-Tetrafluoropropene is found on the following regulatory lists:

Europe EC Inventory

##### Polymeric Diphenylmethane Diisocyanate is found on the following regulatory lists:

EU REACH Regulation (EC) No 1907/2006 - Annex XVII - International Agency for Research on Cancer (IARC) -  
Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Agents Classified by the IARC Monographs

##### Nitrogen is found on the following regulatory lists:

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

#### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

##### ECHA summary:

Ingredient	CAS number	Index No	ECHA Dossier
1,3,3,3-tetrafluoropropene	29118-24-9	Not available	01-0000019758-54-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Flam. Gas 1; Liq.; Skin Irrit. 2; Eye Irrit. 2; Resp. STOT SE 3	GHS02; GHS07; GHS04; Dgr	H220; H280; H315; H319; H335
2	Flam. Gas 1; Liq.; Skin Irrit. 2; Eye Irrit. 2; Resp. STOT SE 3	GHS02; GHS07; GHS04; Dgr	H220; H280; H315; H319; H335
1	Liq.	GHS04; Wng	H280
2	Liq.	GHS04; Wng	H280

**EUOROF PU INSULATION SPRAY ADHESIVE**  
SAFETY DATA SHEET



Reference No: SDS-AP009 Version: 2.0  
Date of issue: 02/01/2024 Page: 16 of 18

1	Liq.; Flam. Gas 1; Acute Tox. 4; Aquatic Chronic 3	GHS04; Wng; GHS02; Dgr	H280; H220; H412
2	Liq.; Flam. Gas 1; Acute Tox. 4; Aquatic Chronic 3	GHS04; Wng; GHS02; Dgr	H280; H220; H412
Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.			

Ingredient	CAS number	Index No	ECHA Dossier
Polymeric Diphenylmethane Diisocyanate	9016-87-9	Not available	01-2119457024-46-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Skin Irrit. 2; Eye Irrit. 2; Acute Tox. 2; Resp. Sens. 1; Resp. STOT SE 3; STOT RE 2; Skin Sens. 1; Carc. 2; Eye Irrit. 2; Resp. Sens. 1; Resp. STOT SE 3; STOT RE 2; Skin Sens.	GHS08; GHS06; Dgr; GHS07; Wng GHS08; GHS06; Dgr;	H315; H319; H330; H334; H335; H373; H317; H351 H319; H334; H335; H373; H317;
2	1; Carc. 2; Acute Tox. 4; Acute Tox. 4; Skin Corr. 1B; Aquatic Chronic 1; Acute Tox. 1; Muta. 2	GHS07; Wng; GHS05; GHS09	H351; H302; H312; H314; H330; H341; H410
Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.			

Ingredient	CAS number	Index No	ECHA Dossier
Nitrogen	7727-37-9.	Not available	Not available

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Comp.; Skin Sens. 1; Eye Irrit. 2; Aquatic Acute 1; Aquatic Chronic 1	GHS04; Wng; GHS09; GHS07	H280; H317; H319; H410
2	Comp.; Ref. Liq.; Liq.; Diss.; Skin Irrit. 2; Eye Irrit. 2; Acute Tox. 4; Resp. STOT SE 3; Muta. 1B; Carc. 1A; Comp.; Skin Sens. 1; Aquatic Acute 1; Aquatic Chronic 1	GHS04; Wng; GHS08; GHS07; Dgr; GHS09	H280; H281; H315; H319; H332; H335; H340; H350; H317; H410
Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.			

National Inventory	Status
Australia - AIIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (polymeric diphenylmethane diisocyanate; nitrogen)
China - IECSC	No (1,3,3,3-tetrafluoropropene)
Europe - EINEC / ELINCS / NLP	No (1,3,3,3-tetrafluoropropene; polymeric diphenylmethane diisocyanate)
Japan - ENCS	No (nitrogen)
Korea - KECI	Yes
New Zealand - NZIoC	No (1,3,3,3-tetrafluoropropene)
Philippines - PICCS	No (1,3,3,3-tetrafluoropropene)
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (1,3,3,3-tetrafluoropropene)
Vietnam - NCI	Yes
Russia - FBEPH	No (1,3,3,3-tetrafluoropropene)
Legend:	Yes = All CAS declared ingredients are on the inventory. No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets).



## 16. OTHER INFORMATION

### Full text Risk and Hazard codes:

H220 Extremely flammable gas.  
H281 Contains refrigerated gas; may cause cryogenic burns or injury.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H330 Fatal if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H340 May cause genetic defects.  
H341 Suspected of causing genetic defects.  
H350 May cause cancer.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

### SDS version summary:

Version	Date of Update	Section Updated
2.0	30/01/2023	Template Change

### Other information:

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection  
EN 340 Protective clothing  
EN 374 Protective gloves against chemicals and micro-organisms  
EN 13832 Footwear protecting against chemicals  
EN 133 Respiratory protective devices

### Definitions and abbreviations:

PC—TWA: Permissible Concentration-Time Weighted Average  
PC—STEL: Permissible Concentration-Short Term Exposure Limit  
IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit.  
IDLH: Immediately Dangerous to Life or Health Concentrations  
ES: Exposure Standard  
OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index  
AIIIC: Australian Inventory of Industrial Chemicals  
DSL: Domestic Substances List  
NDSL: Non-Domestic Substances List  
IECSC: Inventory of Existing Chemical Substance in China  
EINECS: European Inventory of Existing Commercial chemical Substances  
ELINCS: European List of Notified Chemical Substances  
NLP: No-Longer Polymers  
ENCs: Existing and New Chemical Substances Inventory  
KECI: Korea Existing Chemicals Inventory  
NZIoC: New Zealand Inventory of Chemicals  
PICCS: Philippine Inventory of Chemicals and Chemical Substances

**EUROROOF PU INSULATION SPRAY ADHESIVE**  
SAFETY DATA SHEET

Reference No: SDS-AP009      Version: 2.0  
Date of issue: 02/01/2024      Page: 18 of 18



TSCA: Toxic Substances Control Act  
TCSI: Taiwan Chemical Substance Inventory.  
INSQ: Inventario Nacional de Sustancias Químicas  
NCI: National Chemical Inventory  
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

The contents and format of this SDS are in accordance with EEC Commission Directive 1999/45/EC, 67/548/EC, 1272/2008/EC and EEC Commission Regulation 1907/2006/EC (REACH) Annex II.

**DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

