

1. Identification of the substrate/preparation and of the company/undertaking

1.1. Product identifier

Trade name/designation : CALTECH UV WALKWAY COAT

1.2. Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Product is not intended for consumer use.

1.3. Manufacturer/Supplier

Supplier:
Alumasc Exterior Building Products Ltd
White House Works, Bold Road, Sutton, St Helens, Merseyside, WA9 4JG. United Kingdom
Tel: +44 (0)1744 648400 E-mail: roofing@alumasc-exteriors.co.uk

1.4. Emergency telephone number

Emergency telephone : Alumasc 01744 648 400
(Mon-Thur - 08.30-17.00 Fri - 08.30-16.00)

2. Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single, exposure Category 3, Respiratory system	H335: May cause respiratory irritation.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Chronic aquatic toxicity, Category 2	H411: Toxic to aquatic life with long lasting effects.

See Section 16 for the full text of the H statements declared above.
See Section 11 for more detailed information on health effects and symptoms.

2.2. Labelling according to Regulation (EU) 1272/2008

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements

: EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements
Prevention

: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.

Response

: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Hazardous components which must be listed on the label:

265-199-0 Hydrocarbons, C9, aromatics
931-312-3 Isophorondiisocyanate homopolymer
261-879-6 bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate
Pentamethyl piperidylsebacate
223-861-6 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
201-039-8 dibutyltin dilaurate

Additional Labelling:

Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).
This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

3. Composition and information about the components

3.1. Substance

Mixture

3.2. Mixture

Chemical name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Hydrocarbons, C9, aromatics 64742-95-6 265-199-0 01-2119455851-35-XXXX	Flam. Liq.3; H226 STOT SE3; H335, H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 25 - < 50
Isophorondiisocyanate homopolymer 53880-05-0 931-312-3 500-125-5 01-2119488734-24-XXXX Contains: 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate <= 0,49%	Skin Sens.1; H317 STOT SE3; H335	>= 10 - < 20
bis[2-[2-(1-methylethyl)-3- oxazolidinyl]ethyl] hexane-1,2- diylbiscarbamate 59719-67-4 261-879-6 01-2119983487-19-XXXX	Eye Irrit.2; H319 Skin Sens.1B; H317 Aquatic Chronic2; H411	>= 5 - < 10
xylene 1330-20-7 215-535-7 01-2119488216-32-XXXX	Asp. Tox.1; H304 Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315	>= 2,5 - < 5

Chemical name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
ethylbenzene 100-41-4 202-849-4 01-2119489370-35-XXXX	Flam. Liq.2; H225 Acute Tox.4; H332	>= 1 - < 2,5
Diphenyl tolyl phosphate MCS 907-387-3 01-2119511174-52-XXXX	Aquatic Acute1; H400	>= 1 - < 2,5
Pentamethyl piperidylsebacate 01-2119491304-40-XXXX Contains: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	Skin Sens.1A; H317 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,1 - < 0,25
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate 4098-71-9 223-861-6 01-2119490408-31-XXXX	Acute Tox.1; H330 Skin Irrit.2; H315 Eye Irrit.2; H319 Resp. Sens.1; H334 Skin Sens.1; H317 STOT SE3; H335 Aquatic Chronic2; H411	>= 0,1 - < 0,25
dibutyltin dilaurate 77-58-7 201-039-8 01-2119496068-27-XXXX	Skin Corr.1C; H314 Skin Sens.1; H317 Muta.2; H341 Repr.1B; H360FD STOT SE1; H370 STOT RE1; H372 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,1 - < 0,25

Remarks : Substances with a workplace exposure limit

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. First-aid measures

4.1 Description of first aid measures

General	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
Eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
Inhalation	:	Move to fresh air. Consult a physician after significant exposure.
Skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
Ingestion	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	:	Aspiration may cause pulmonary oedema and pneumonitis. Cough Respiratory disorder Allergic reactions Erythema Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms.
Risks	:	Risk of serious damage to the lungs (by aspiration). irritant effects sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically.
-----------	---	------------------------

5. Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical

Unsuitable extinguishing media : Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Additional information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentrations.
Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

7. Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

8. Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters *	Basis *
xylene	1330-20-7	TWA	50 ppm 220 mg/m ³	GB EH40
		STEL	100 ppm 441 mg/m ³	GB EH40
		TWA	50 ppm 221 mg/m ³	2000/39/EC
		STEL	100 ppm 442 mg/m ³	2000/39/EC
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
		STEL	200 ppm 884 mg/m ³	2000/39/EC
		TWA	100 ppm 441 mg/m ³	GB EH40
		STEL	125 ppm 552 mg/m ³	GB EH40
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,02 mg/m ³	GB EH40
		STEL	0,07 mg/m ³	GB EH40
dibutyltin dilaurate	77-58-7	TWA	0,1 mg/m ³	GB EH40
		STEL	0,2 mg/m ³	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650mmol/mol creatinine (Urine)	Post shift	GB EH40 BAT

DNEL

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane- : End Use: Workers
Exposure routes: Inhalation

1,2-diylbiscarbamate

Potential health effects: Long-term systemic effects
Value: 29,4 mg/m³

End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 6,25 mg/m³

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Long-term systemic effects

PNEC

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate

: Fresh water
Value: 0,0186 mg/l

Marine water
Value: 0,00186 mg/l

Fresh water sediment
Value: 0,709 mg/kg

Marine sediment
Value: 0,0709 mg/kg

Soil
Value: 1,131 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (0,4 mm),

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm),
breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor (Type A) and particulate filter
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
- Environmental exposure controls
- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	various
Odour	:	aromatic
Odour Threshold	:	No data available
Flash point	:	41 °C
Autoignition temperature	:	465 °C
Lower explosion limit (Vol-%)	:	0,8 %(V)
Upper explosion limit (Vol-%)	:	7 %(V)
Flammability	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
pH	:	No data available
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Vapour pressure	:	4,9996 hPa

Density	:	ca.1,1 g/cm ³ at 20 °C
Water solubility	:	insoluble
Partition coefficient: noctanol /water	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	>7 mm ² /s at 40 °C
Relative vapour density	:	ca. 1
Evaporation rate	:	ca. 0,6
		Note: See user defined free text

9.2 Other information

No additional information.

10. Stability and reactivity

10.1 Reactivity:

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability:

The product is chemically stable.

10.3 Possibility of hazardous reactions:

Hazardous reactions : Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid:

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials:

Materials to avoid : No data available

10.6 Hazardous decomposition products:

Hazardous decomposition products : No decomposition if stored and applied as directed.

11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics :

Acute oral toxicity : LD50 Oral rat: > 2.000 mg/kg
Acute dermal toxicity : LD50 Dermal rabbit: > 2.000 mg/kg

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate :

Acute oral toxicity : LD50 Oral rat: > 5.000 mg/kg
Acute dermal toxicity : LD50 Dermal rabbit: > 2.000 mg/kg

xylene :

Acute dermal toxicity : Acute toxicity estimate : 1.100 mg/kg
Method: Converted acute toxicity point estimate

Diphenyl tolyl phosphate MCS :

Acute oral toxicity : LD50 Oral rat: > 5.000 mg/kg
Acute dermal toxicity : LD50 Dermal rat: > 2.000 mg/kg

Pentamethyl piperidylsebacate :

Acute oral toxicity : LD50 Oral rat: 3.230 mg/kg

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate :

Acute oral toxicity : LD50 Oral rat: 4.814 mg/kg
Acute inhalation toxicity : LC50 rat: 0,031 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Acute dermal toxicity : LD50 Dermal rat: > 7.000 mg/kg

dibutyltin dilaurate :

Acute oral toxicity : LD50 Oral rat: 2.071 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking. causes skin irritation.

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

12. Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9, aromatics :

Toxicity to algae : 2,6 - 2,9 mg/l, 72 h, Pseudokirchneriella subcapitata (green algae)

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate :

Toxicity to daphnia and other aquatic invertebrates : EC50: 87,1 mg/l, 48 h, Daphnia magna (Water flea)

Toxicity to algae : EC50: 18,6 mg/l, 72 h, Scenedesmus capricornutum (fresh water algae)

Pentamethyl piperidylsebacate :

Toxicity to fish : LC50: 0,97 mg/l, 96 h, Fish

dibutyltin dilaurate :

Toxicity to fish : LC50: 3,1 mg/l, 96 h, Fish

Toxicity to daphnia and other aquatic invertebrates : EC50: 1 mg/l, 48 h, Daphnia

Toxicity to algae : EC50: 1 - 10 mg/l, 72 h, Selenastrum capricornutum (green algae)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

13. Disposal considerations

13.1 Waste treatment methods

Product

: The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.




European Waste Catalogue

: 07 01 04* other organic solvents, washing liquids and mother liquors

Contaminated packaging

: 15 01 10* packaging containing residues of or contaminated by dangerous substances

14. Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	Paint related material	Paint related material (solvent naphtha)	Paint related material
14.3 Transport hazard class(es)	3. 	3. 	3. 
14.4 Packing group	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.
Additional information	ADR Tunnel code: (D/E)	Emergency schedules (EmS): F-E + S-E Marine pollutant (P) Yes	

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted (Naphtha (petroleum), hydrotreated heavy)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH Information : All substances contained in our Products are
- preregistered or registered by our upstream suppliers, and/or
- preregistered or registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

VOC-CH (VOCV) : 32,26 %
VOC-EU (solvent) : 32,26 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002
Control of Substances Hazardous to Health Regulations 2002
The Management of Health and Safety at Work Regulations 1999
Health and Safety at Work Act 1974
Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

16. Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H330 : Fatal if inhaled.
H332 : Harmful if inhaled.
H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H341 : Suspected of causing genetic defects.
H360FD : May damage fertility. May damage the unborn child.
H370 : Causes damage to organs if swallowed.
H372 : Causes damage to organs through prolonged or repeated exposure if swallowed.

H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Muta.	Germ cell mutagenicity
Repr.	Reproductive toxicity
Resp. Sens.	Respiratory sensitisation
Skin Corr.	Skin corrosion
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure
ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal doses (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

The contents and format of this SDS are in accordance with EEC Commission Directive 1999/45/EC, 67/548/EC, 1272/2008/EC and EEC Commission Regulation 1907/2006/EC (REACH) Annex II.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.