

Product Datasheet

Hydrogard 20

Sheet No: PD206FR
Issued: July 2021
Pages: 1 of 1

Description

Hydrogard 20 is a polyester reinforced, oxidised bituminous protection sheet, with a sanded finish to both sides.

Use

As a protection sheet for Hydrotech Monolithic Membrane 6125.

Application

Laid directly into the second coat of Hydrotech, with 75mm Hydrotech sealed overlaps.

Storage

Store upright in a clean, dry location, away from heat sources.

Product Data

Thickness	2.0mm
Width	1.0m
Length	20.0m
Weight	1.8kg/m ²
Weight per roll	36kg

Performance Data

Tensile Strength – longitudinal	>450 N/50mm
Tensile Strength – transverse	>400 N/50mm
Elongation at break – longitudinal	>30%
Softening point	90°C
Cold bend	-10°C

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.